



MAXI-TUBE® Grey Colour Match

MINIMUM NET WEIGHT 300g

MAXI-TUBE® Grey paint has been specifically formulated to colour match MAXI-TUBE®.

MAXI-TUBE® Grey is required over the Zinc-rich epoxy or Metalspray base coat to match the parent MAXI-TUBE® alloy colour.



ph 1300 677 266
www.maxitube.com.au

DIRECTIONS FOR USE

BEFORE APPLICATION: Shake vigorously for two minutes before and at intervals during painting to obtain correct colour and gloss. The mixing ball will rattle around inside.

SURFACE PREPARATION AS A TOP COAT: To ensure maximum paint adhesion, MAXI-TUBE® Grey should be sprayed over the wet Zinc-rich epoxy base protection coat. If MAXI-TUBE® Grey is placed over a dry Zinc-rich epoxy base coat or metal spray, lightly abrade the surface to remove all traces of oil, wax, grease and loose particles with a cleaning solvent prior to application.

APPLICATION: The nozzle produces a fan shaped spray similar to a professional spray gun. Spray with smooth, even horizontal strokes about 10-15cm from the job. Spray several light coats instead of one heavy coat. Do not use aerosol spray when coating over metal spray. Use an airless spray, brush or roller over metal spray with MAXI-TUBE® Grey from a paint tin.

In cold weather, warm can to room temperature for optimum spraying performance. Allow overnight drying before handling. If in doubt, test first in a non-critical area.

AFTER SPRAYING: Invert can and press valve until mist clears. If nozzle is blocked, clean with lacquer thinners or replace. Point the nozzle away from you when replacing.

STORAGE: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

DISPOSAL: Dispose of contents and container in accordance with all local, regional, national and international regulations.

DANGER

Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents and container in accordance with all local, regional, national and international regulations. Repeated exposure may cause skin dryness or cracking.

FIRST AID

EYE CONTACT: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

INHALATION: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

SKIN CONTACT: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

INGESTION: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.



www.orrconsteel.com.au

Product Code B167525

Manufactured by:

PPG Industries Australia Pty Limited

ABN 82 055 500 939 Locked Bag 888

CLAYTON SOUTH Victoria 3169

MAXI-TUBE® is a registered trademark

of Orrcon Steel. Orrcon Steel is a wholly

owned subsidiary of Bluescope Steel Limited.

UN1950

Class 2.1 Packing group - AEROSOLS

Hazchem code: Not applicable.

Emergency telephone number: 1800 883 254

DANGER

Extremely flammable aerosol.

Causes serious eye damage.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.



Reserved for industrial and professional use.

Additional information is listed in the Safety Data Sheet

Contains:

acetone 10 - <30

propane 10 - <30

butane 10 - <30

n-butyl acetate 10 - <30

isobutane 1 - <10

butan-1-ol 1 - <10

xylene 1 - <10

2-methoxy-1-methylethylacetate 1 - <10